




Skygarden 1

Designed by Marcel Wanders, 2007



Halogen - 105W

Suspension luminaire providing diffused lighting. Hemispherical, mechanicallyprocessed cast plaster diffuser, painted white inside. Outer finish: rust, glossy black, glossy white or matte gold. Plaster diffuser support in die-cast aluminum alloy, liquid-painted white. Molded upper bushing in die-cast, polished aluminum alloy, protected with transparent paint on the entire visible part. Upper cable gland and blocking ring nut in black injection-molded PC (polycarbonate). Shaped, galvanized adjustment screws. Transparent, injection-molded, upper and lower silicone shock absorbers. Lamp holder and fixing support in black injection-molded PPS (polyphenylene sulfide). Flashed and blown opal glass diffuser. Molded fixing ring nut in die-cast aluminum alloy with alodine plating. Skygarden 1 frieze in photo-etched and mechanically drawn AISI 304 steel. Molded and galvanized steel ceiling attachment Gray, injection-molded PA6 (Nylon) rose.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Rusty Brown

Main specifications

EAN	8059607012789
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	Halogen
Lamp holders	E27
Ilcos	HSGS
Number of heads	1
Power (W)	105

Physical

Colodi	Rasty Brown
Length (mm)	600
Cord length (mm)	2700
Canopy dimension (mm)	36
Canopy width (mm)	146
Net weight (kg)	13
Package height (mm)	435
Package width (mm)	730
Package length (mm)	730
Package volume (m3)	0.23
IP internal	20

Mounting instructions	业 PDF
Spare Parts	⊥ PDF
Photometric Files	5
LDT / IES	⊥ LDT
Technical Drawin	gs
2D	业 ZIP
3D	业 ZIP
a Bim	⊥ ZIP

https://professional.flos.com/en/global/product/skygarden-1-f0001047/

F0001047





















Schematic light drawing



 Beam Angle: 118°

 h(m)
 E(lx)
 D(m)

 1
 416
 3.36

 2
 104
 6.72

 3
 46
 10.08

 4
 26
 13.44


 5
 17
 16.79

Photometric

Light distribution Symmetric

Electrical

Insulation class	L	
Frequency (Hz)	50/60	
Main voltage (Vac)	220-250	
LED voltage Vf (Vdc)	null	
Dimmable	Yes	
Dimming interface	Remote Dimmable (Dimmer Not Included)	
Batteries inside	No	




NOT INCLUDED

RF29388

LED T46 Lamp E27 20W 2700K Dimmable

Spare Parts



Rust ceiling rose assembly RF6410147
 Skygarden 1 glass diffuser RF6410100
 Kit of 5 or rings RF05382

DOWNLOAD





00000

RF6410147

RF6410100

RF05382

Rust ceiling rose assembly

Skygarden 1 glass diffuser

Kit of 5 or rings