




DEEP

CEILING RECESSED



1.0 LED

LED 7/10W | 350/500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated
CRI >90

0.31kg | IP20 | 0.3° | 36°

90

wire springs 76-79 4-27

CODE	
112161W_	
112161S_	
112161G_	
112161B_	

blade springs 76-79 min 10

CODE	
112161W_C	
112161B_C	

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	530/710	>90	3
3000K	570/770	>90	5
4000K	610/830	>90	6
1800-2850K 16V	330/450	>95	9

ALWAYS USE

power supply | 500mA

CODE	
10W	90214405
15W dim	90224501
20W DALI	90244602

350mA power supplies on page 694

1.0 MR16

QR-CBC51 max. 12W | GU5.3
12V | excl. power supply
aluminium powder coated

0.25kg | IP20 | 0.3°

90

wire springs 76-79 4-27

CODE	
112110W0	
112110S0	
112110G0	
112110B0	

blade springs 76-79 min 10

CODE	
112110W0C	
112110B0C	

ALWAYS USE

power supply | 12V

CODE	
10W dim	90221401
25W dim	90221701
70W dim	90221904

more specs on page 699

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.29kg | IP20 | 0.3°

105

wire springs 76-79 4-27

CODE	
112120W0	
112120S0	
112120G0	
112120B0	

blade springs 76-79 min 10


CODE	
112120W0C	
112120B0C	

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

CODE	
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701



For wireless dimming compatible with Amazon Echo Plus, Philips Hue and Homee see page 239.