





M52 - 2 LED OK 82720 DIM5

24419 8225



 [Bekijk op website](#)

Algemene info

LOCATIE	binnen
INSTALLATIE	Laagspanningssystemen Laagspanningssysteem montage
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.3
RICHTBAARHEID	0° tot 45° zwenkbaar
INFO	2 x LENS FL-20° EXCL.LED POWER SUPPLY 48V-DC

Elektrische info

INGANGSSPANNING	48V-DC
KLASSE	III
DIM TYPE	DALI
ENERGIE KLASSE	F
CERTIFICATEN	CB, ENEC

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	2 x (LED array 6W / CRI>80 / 2700K / 558lm)
SDCM	SDCM2
LED TECHNIEK (LICHTBRON)	1116lm // 12W // 94lm/W
LED TECHNIEK (TOESTEL)	948lm // 14W // 69lm/W

Benodigheden

LED POWER SUPPLY 48V-DC

Voor gedetailleerde montage gegevens, consulteer de handleiding: [24419_8X25_HAND.pdf](#)


M52 - 2 LED OK 82720 DIM5

24419 8225

VERVOLLEDIG UW SPECIFICATIE


LED voedingen

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

7




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

17



21012 0230 LED POWER SUPPLY 48V-DC / 100W

7



21012 0240 LED POWER SUPPLY 48V-DC / 200W

14


M52 - 2 LED OK 82720 DIM5

24419 8225


COMPATIBELE DRAAGSTRUCTUREN

SPLITLINE M52 profile


Beschikbare kleuren




420 52 10 00 SPM52 - PROFILE 1m



420 52 20 00 SPM52 - PROFILE 2m



420 52 30 00 SPM52 - PROFILE 3m



24413 0000 SPM52 - PROFILE



Notes: