## Wireflow free-form

## $\vee$ | 3 | $\wedge$

## 0349

Design By Arik Levy

Wireflow designed by Arik Levy. Hanging lap. The elegant structure of fine cables and LED terminal by Wireflow allows the combination of multiple individual pieces to carry out major graphic lighting installations which generate a visual opportunity of lines and points of light and bring a markedly conceptual character to an intangible product. The electrical connection point can be positioned on the ceiling or wall.

## Model Sheet





	_	
Finish	O4 Black RAL 9005	Lighting effect
		General Lighting
LED temperature color	2700 K / 3000 K / 3500 K	Lamp for general lighting that equally distributes the light in all directions.
Dimming	CASAMBI / DALI 1-10V Push	
Instalation type	Surface Canopy	Photometric Data
Materials	Ceiling rose: Steel Body: Aluminum Rods: Steel	Efficiency40.07%Coordinate SystemCGTotal Flux980.60Maximum Value53.77
Light source	2 x LED 4,48W 350mA	Other Applications
LED	CRI>90 981 lm 109 2700 K / 3000 K / 3500 K	
Driver	Constant Current 350 110~240 V V 50~60 Hz HZ	
	(IP20) [Dimmable] [LED] (IP20) [Bi-volt] [50-60Hz]	
Application	Hanging lamps	
Packaging	1 Box 0.42 m x 0.42 m x 0.25 m Gross weigth 6 Net weigth 5 Vol. 0.0441	

¢ 31 cm

**Optional : Extra cable length** Min. quantity, upcharge and extra lead time apply [EN]

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina Progrés 4-6. 08850 Gavà. Barcelona, Spain.

customer.service@vibia.com vibia.com