Puck wall art

\vee | 3 | \wedge

5486

Design By Jordi Vilardell

Wall sconce formed by two circular bodies with a single electrical connection. Available in different lacquered aluminium and felt finishes.

Model Sheet





Finish	72 Grey D1 & Grey L2 NCS S 7000-N & NCS S 2500-N
	71 Grey Felt L1 & Grey Felt D1
LED temperature color	2700 K / 3500 K / 4000 K
Dimming	1-10V / CASAMBI / PUSH / DALI
Instalation type	Surface Canopy
Materials	Shade: ABS Wall support: Aluminum Ring: Steel Diffuser: Polycarbonate
Light source	2 x LED STRIP 12,6W 700mA
LED	CRI>90 2871.9 lm 94.22 2700 K / 3500 K / 4000 K
Driver	Constant Current 700 110~240 V V 50~60 Hz HZ
Remarks	A maximum of 8 modules can be connected to a single connection point. For bigger compositions, check connection system.
	[] \F/ Dimmable [IP20] [Bi-volt] 50-60Hz
Application	Wall Lamps
Packaging	1 Box 0.68 m x 0.68 m x 0.25 m Gross weigth 11.35 Net weigth 5.45 Vol. 0.1156

Lighting effect

General Lighting Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Total Flux


Maximum Value

Photometric Data Efficiency Coordinate System

34.56 lm/W CG 1024.92 lm 192.03 cd

Other Applications





	Bi-volt 5
Application	Wall Lam
Packaging	1 Box 0.68 m x Gross wei Net weigt Vol. 0.1156

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina Progrés 4-6. 08850 Gavà. Barcelona, Spain. International T +34 934 796 971 Spain / Portugal T +34 934 796 970 customer.service@vibia.com vibia.com