Puck wall art



5481


Design By Jordi Vilardell

Wall sconce formed by two circular bodies with a single electrical connection. Available in different lacquered aluminium and felt finishes.

Model Sheet







Finish 71 Grey Felt L1 & Grey Felt D1 15 Grey L2



NCS S 2500-N 28 Brown M1 NCS S 4020-Y60R

LED temperature

Dimming

2700 K / 3500 K / 4000 K

TRIAC / PUSH / CASAMBI / DALI

Instalation type Surface Canopy

Materials

Shade: ABS

Wall support: Aluminum Diffuser: Polycarbonate

Light source 2 x LED STRIP 12,6W 700mA

E

LED CRI>90 2871.9 lm 94.22 2700 K / 3500 K / 4000 K

Driver Constant Current 700 110~240


V V 50~60 Hz HZ

Remarks A maximum of 8 modules can be connected to a single connection

point. For bigger compositions, check connection system.











Application Wall Lamps

Packaging

0.68 m x 0.68 m x 0.2 m Gross weigth 5.2 Net weigth 4.15

Vol. 0.0924

Lighting effect

General Lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Data

56.12 lm/W Efficiency Coordinate System CG 1664.84 lm **Total Flux** 365.39 cd Maximum Value

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty