

# FLOS

■ F0279000 Black

## Noctambule Suspension 6 Low Cylinder

Designed by Konstantin Grcic, 2019


63W - 2054lm - 2700K



Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

EAN	8059607000748
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	63
System flux (lm)	2054

### Physical

Colour	Black
Length (mm)	250
Cord length (mm)	4000
Canopy dimension (mm)	45
Canopy width (mm)	187
Net weight (kg)	23.9
Package height (mm)	0
Package width (mm)	0
Package length (mm)	0
Package volume (m3)	0.42
IP internal	20

### Download


Mounting instructions	↓ PDF
Mounting instructions	↓ PDF
Spare Parts	↓ PDF

### Photometric Files


LDT / IES	↓ ZIP
-----------	-------

### Technical Drawings

3D	↓ ZIP
🔒 Bim	↓ ZIP



## Schematic light drawing



Luminous flux luminaire  
286 lm

## Photometric


Lighting type	Total
Light distribution	Symmetric
CCT (K)	2700

## Electrical


Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120-277
LED voltage Vf (Vdc)	null
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only)  
light source by a  
professional



Replaceable control  
gear by a professional

## Spare Parts



- |     |  |           |
|-----|--|-----------|
| 01. | Power supply kit for Arrangements small & Noctambule | RF0410500 |
| 02. | Led dimmer kit                                       | RF0410300 |
| 03. | Noctambule ceiling rose cover                        | RF27422   |
| 04. | Suspension attack                                    | F0253030  |
| 05. | Ring led diffuser                                    | RF27498   |
| 06. | Fixing screws kit                                    | RF0254100 |
| 07. | Noctambule Low Cylinder                              | F0254000  |
| 08. | Terminal ring  | F0258030  |

**DOWNLOAD**



RF0410500  
Power supply kit for  
Arrangements small &  
Noctambule



RF0410300  
Led dimmer kit



RF27422  
Noctambule ceiling rose cover



F0253030  
Suspension attack



RF27498  
Ring led diffuser



RF0254100  
Fixing screws kit



F0254000  
Noctambule Low Cylinder



F0258030  
Terminal ring