


Tube

6165

Design By Ichiro Iwasaki

VIBIA

Model Sheet



Optional: Extra cable length
Min. quantity, upcharge and extra lead time apply [EN]

Finish


- 10 White
NCS S 0300-N
- 15 Grey L2
NCS S 2500-N
- 24 Beige M1
NCS S 2005-Y50R
- 37 Terra Red
NCS S 4040-Y70R
- 16 Grey M1
NCS S 4500-N
- 21 Black Grey
NCS S 7000-N

LED temperature color 2700 K / 3000 K / 3500 K

Dimming DALI 1-10V Push / CASAMBI / DALI / NO DRIVER

Installation type Surface Free Wire / Remote Micro / Surface Canopy / Built-in XS

Materials LED support: Aluminum
Tube: Steel. Black finish.
Ceiling rose: Steel

LED  CRI>90 3480 lm 139,2
2700 K / 3000 K / 3500 K

Driver Constant Current 700 110~240
V V 50~60 Hz HZ

  **Dimmable** **LED**
IP20 **Bi-volt** **50-60Hz**

Application Hanging lamps

Packaging 2 Box
0,248 m x 0,403 m x 0,403 m
Gross weight 4,3
Net weight 1,65
Vol. 0,0447

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.

Photometric Data

Efficiency	51,14 lm/W
Coordinate System	CG
Total Flux	1447,46 lm
Maximum Value	576,19 cd

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com