# Wireflow free-form



### 0350


Design By Arik Levy

Wireflow designed by Arik Levy. Hanging lap. The elegant structure of fine cables and LED terminal by Wireflow allows the combination of multiple individual pieces to carry out major graphic lighting installations which generate a visual opportunity of lines and points of light and bring a markedly conceptual character to an intangible product. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements. The electrical connection point can be positioned on the ceiling or wal

## Model Sheet







Optional: Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Finish



04 Black **RAL 9005** 

LED temperature color

2700 K / 3000 K /

3500 K

Dimming

DALI 1-10V Push / CASAMBI

Instalation type

Surface Canopy

Materials

Ceiling rose: Steel Body: Aluminum Rods: Steel

Light source

3 x LED 4,48W 350mA

D

LED

CRI>90 1471 lm 109 2700 K / 3000 K / 3500 K

Driver

Constant Current 350 110~240

V V 50~60 Hz HZ

IP20 Bi-volt 50-60Hz

**Application** 

Hanging lamps

**Packaging** 

0.42 m x 0.42 m x 0.25 m Gross weigth 6 Net weigth 5

Vol. 0.0441

#### Lighting effect

#### **General Lighting**

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency Coordinate System **Total Flux** Maximum Value

40.11% CG 1470.80 53.87

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty