




GALEN 120

SP LED PROFILE Outdoor Single Colour CCT switch 3000/4000K IP67

Thanks to the integrated mounting bracket and the splash-proof connection cables, the GALEN LED profile can be installed quickly and easily on walls, floors, or ceilings. It is most suitable as a form of lighting for displays and signs. Added to this is the practical CCT switch, which provides added flexibility as it allows the light colour to be adjusted between 3000K (warm white) and 4000K (neutral white) using an external switch. Robustly made and featuring high-performance LEDs, GALEN is perfect for creating effective or functional lighting in the outdoor areas of shops, hotels, restaurants, or in commercial buildings.



TECHNICAL DATA

Item no.:	1003448
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	900 mA/V
Vertical tilting range	180 °
Width	120.0 cm
Height	6.2 cm
Depth	11.3 cm
Net weight	2.5 kg
Gross weight	2.675 kg
IP Code	IP 65
Safety class	I
Impact resistance class	IK03
Impact resistance	0,3499999999999998 Joule
Assembly	Surface
Assembly details	Ceiling,Ground,Wall
Number of through-wires	10
Wattage	34.0 W
Lumen	3100 lm
Color	anthracite
CRI	>80
Binning	6
LXXBXX data	70/50

Accessories

231960	CONNECTION CABLE , for GALEN outdoor wall light, black, 5 m
231961	CONNECTION CABLE , for GALEN outdoor wall light, black, 1 m

Service life	54000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C

Notes
