Wireflow free-form



0356


Design By Arik Levy

Wireflow designed by Arik Levy. Hanging lap. The elegant structure of fine cables and LED terminal by Wireflow allows the combination of multiple individual pieces to carry out major graphic lighting installations which generate a visual opportunity of lines and points of light and bring a markedly conceptual character to an intangible product. The electrical connection point can be positioned on the ceiling or wall.

Model Sheet







Optional: Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Finish

color

RAL 9005

04 Black

2700 K / 3000 K / LED temperature 3500 K

Dimming CASAMBI / DALI 1-10V Push

Instalation type Surface Canopy

Materials Ceiling rose: Steel Body: Aluminum

Rods: Steel

Light source 7 x LED 4,48W 350mA

D

LED CRI>90 3432 lm 109

2700 K / 3000 K / 3500 K

Constant Current 350 110~240 Driver V V 50~60 Hz HZ

Dimmable LED IP20

Bi-volt 50-60Hz

Application Hanging lamps

Packaging

0.42 m x 0.42 m x 0.25 m Gross weigth 7 Net weigth 6 Vol. 0.0441

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

40.11% Efficiency Coordinate System CG 3432 **Total Flux** Maximum Value 53.92

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty