
BARI 8037 SKU 1047006



PRODUCT SPECIFICATION

GENERAL


| FINISH: | Painted Black | CABLE LENGTH: | Not Applicable |
|---------------------------|--------------------------|----------------------------|--|
| MAIN MATERIAL: | Metal - Zinc | GROSS WEIGHT: | 0.7 (kg) |
| DIMENSIONS: | H: 205mm W: 40mm D: 60mm | CLASS: | CE (Class II) |
| INSTALLATION ORIENTATION: | Wall Mount - Vertical | IP RATING: | IP44 |
| CUT OUT HOLE: | Not Applicable | BATHROOM ZONE: | Zone 2, 3 |
| RECESS DEPTH: | Not Applicable | VOLTAGE: | |
| FIRE RATING: | Not Applicable | PRODUCT F MARK: | Mains 230 (V) Suitable for mounting on flammable materials |
| LAMP | | | |
| LIGHT SOURCE: | G9 | MACADAM ELIPSE: | Not Applicable |
| MAXIMUM WATTAGE: | 40W Max | UGR: | Not Applicable |
| MAXIMUM LAMP LENGTH: | To Be Advised | BEAM ANGLE: | Not Applicable |
| LAMP INCLUDED? | No | TILT ADJUSTMENT ANGLE: | Not Applicable |
| LUMINOUS FLUX: | Lamp Dependent | ROTATION ADJUSTMENT ANGLE: | Not Applicable |
| COLOUR TEMP: | Lamp Dependent | AVERAGE LIFESPAN: | Lamp Dependent |
| CRI: | Lamp Dependent | L70: | Not Applicable |
| R9: | Lamp Dependent | | |
| ELECTRICAL | | | |
| SWITCHED: | No | SUPPLY FREQUENCY: | Not Applicable |
| DIMMABLE: | Yes | DRIVER/BALLAST VOLTAGE: | Not Applicable |
| DIMMING METHOD: | Lamp Dependent | DRIVER AVERAGE LIFESPAN: | Not Applicable |
| DRIVER OUTPUT CURRENT: | Not Applicable | EFFICACY: | Lamp Dependent |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER/BALLAST INCLUDED? | Not Applicable |
| | | | |
| ADDITIONAL INFORM | MATION | | C |


ADDITIONAL INFORMATION





BOX QUANTITY X12

PRODUCT ELEVATIONS











sales@astrolighting.com