



## **KTribe F3 Outdoor Panama**


Designed by Philippe Starck, 2007



Light source not included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



## Main specifications

Mounting	Floor
Environments	Outdoor wet location
Light Source Type	Bulb
Lamp holders	E27
Ilcos	HSGS
Number of heads	1
Power (W)	230

# Physical

Colour	Panama
Orientation	Fixed
Length (mm)	580
Net weight (kg)	24
Package height (mm)	0
Package width (mm)	0
Package length (mm)	0
Package volume (m3)	0.78
IP internal	44
IP external	44

# Download

Mounting instructions	<b>⊥</b> PDF
Mounting instructions	<b>⊥</b> PDF

## Photometric Files

LDT / IES



# **Technical Drawings**

2D	$\overline{\mathbf{A}}$	ZIP
3D	业	ZIP









# Schematic light drawing



Beam Angle DIR: 85°		
h(m)	E(lx)	D(m)
1	195	1.82
2	49	3.64
3	22	5.46
4	12	7.28
5	8	9.10

### Photometric

Lighting type	Direct
Light distribution	Symmetric
Beam angle C0-180 (°)	85
Beam angle C90-270 (°)	85

### Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-250
Dimmable	Yes
Dimming interface	Remote Dimmable (Dimmer Not Included)
Emergency type	No
Batteries inside	No
Charging min time	NO

### **Notes**

Light source not included. HSGS E27: 1x250W or 1 LED: 21W - 2450 lm - 3000K We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.





**NOT INCLUDED** 

RF30429

LED Opal Lamp E27 21W 2700K A65 Dimmable NOT INCLUDED

RF26998

LED 21W E27 2450lm 3000K DIMMER



02. Kit of 5 white feed pads for base RF3020100



RF3020100

Kit of 5 white feed pads for base