
ASCOLITRACK 6168

astro





PRODUCT SPECIFICATION

GENERAL

FINISH: Textured Black CABLE LENGTH: Not Applicable MAIN MATERIAL: Metal - Aluminium **GROSS WEIGHT:** 0.50 (Kg) H: 141mm DIA: 57mm **DIMENSIONS:** CLASS: CE (Class II) INSTALLATION ORIENTATION: Ceiling Mount IP RATING: IP20 Not Applicable **CUT OUT HOLE: BATHROOM ZONE:** Zone 3 **RECESS DEPTH:** Not Applicable **VOLTAGE:** Mains 230 (V) FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting

LAMP

LIGHT SOURCE: GU10 MACADAM ELIPSE: Not Applicable 50W Max MAXIMUM WATTAGE: UGR: Not Applicable MAXIMUM LAMP LENGTH: 57mm **BEAM ANGLE:** Not Applicable LAMP INCLUDED? No TILT ADJUSTMENT ANGLE: 90 (Degrees) **LUMINOUS FLUX:** Lamp Dependent **ROTATION ADJUSTMENT ANGLE:** 330 (Degrees) **COLOUR TEMP:** AVERAGE LIFESPAN: Lamp Dependent Lamp Dependent CRI: Lamp Dependent L70: Not Applicable

ELECTRICAL

R9:

SWITCHED: SUPPLY FREQUENCY: No Not Applicable DIMMABLE: Yes DRIVER/BALLAST VOLTAGE: Not Applicable DIMMING METHOD: Lamp Dependent DRIVER AVERAGE LIFESPAN: Not Applicable **DRIVER OUTPUT CURRENT:** Not Applicable EFFICACY: Lamp Dependent DRIVER OUTPUT VOLTAGE: DRIVER/BALLAST INCLUDED? Not Applicable Not Applicable

Lamp Dependent

ADDITIONAL INFORMATION



BOX QUANTITY x 12

CE

on flammable materials

