


MÉDARD RECESSED 70 LED WARM DIM GE

Médard recessed broadens the variety of applications. In contrast to the rest of the family, Médard recessed's light source is fixed, emanating a medium or flood beam angle. Hospitality environments including wellness centers, and high-end residential spaces, including bathrooms, will be spot-on locations for this IP55-rated new family member.

Art. Nr. 11551532

SPECIFICATIONS

Lamp	1x LED Module 12W
Gear / Transfo	LED gear not incl.
Cut-out size	ø 65 h 95
Weight	0.26kg
Min. distance	0.1 m
Power supply	350mA
IP	IP55
Glow wire test	960°
Lifetime	50000 hrs
CRI	90
CIE flux code	99/100/100/100/71
Lumen	680 Lm
Efficacy	57 Lm/W
UGR	19
Adjustability	Not Applicable



Available label
<http://supemodular.com/assets/TYPE2.pdf>

	WARM DIM 1800K - 3000K / CRI 90+	
	MEDIUM 25°	FLOOD 40°
black struc	11551432	11551532
white struc	11551409	11551509



MÉDARD RECESSED 70 LED WARM DIM GE

ACCESSORIES

HUE-MODULE

13190130 | HUE DIM CIRCUIT MODULE 150-300W 0/1-10V

HUE-BRIDGE

70000616 | HUE BRIDGE EU

70000617 | HUE BRIDGE UK

HUE-DEVICE

70000615 | HUE TAP SWITCH

70000154 | NIKO PURE SWITCH FOR HUE - WHITE STEEL

70000155 | NIKO PURE SWITCH FOR HUE - BLACK STEEL

70000152 | HUE DIMMER SWITCH

70008054 | HUE SENSOR

